Product FLEETWOOD ULTRA TOUGH OXIDE - RED

Revision date 15 January 2021

Revision 3



Safety Data Sheet (SDS)

according to Regulation (EC) No. 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name FLEETWOOD ULTRA TOUGH OXIDE - RED

Other means of identification UFI: TJ90-200G-R00X-8P8U

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified usesPaint or paint related material.Uses advised againstNo uses advised against are identified.

1.3 Details of the supplier of the safety data sheet

Supplier FSW Coatings Ltd

Virginia Co Cavan Ireland

Tel: 353 49854 7209

Contact person info@fsw.ie

1.4 Emergency telephone number

Emergency telephone

National emergency telephone

number

+ 353 49854 7209 (Between 0900 and 1700 hrs Monday-Friday)

Outside those hours, contact National Poisons Information Centre, Beaumont Hospital. Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare

Professionals: +353 (1) 809 2566 (24 hour service)

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and chemical hazards Flam. Liq 3- H226

Human health STOT SE 3 - H336, Skin. Sens 1 A- H317

Environment Not classified

2.2 Label elements

Contains Cobalt bis(2-ethylhexanoate)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

nonane

Label in accordance with (EC) no.

1272/2008



Signal word Warning

 $\mbox{{\it Hazard statements}} \qquad \qquad \mbox{{\it H226 Flammable liquid and vapour}}.$

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

Precautionary statements Prevention

P210 Keep away from heat/ sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves/ protective clothing/eye protection/face protection.

Response

P370 + P378 In case of fire: Use dry chemical, CO2, water spray (fog) or foam for extinction. **Storage**

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

2.3 Other hazards

None known.

Section 3: Composition/information on ingredients

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Regulation (EC) No 1272/2008	%
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: EC No.: 919-857-5 REACH Reg No.: 01-2119463258-33-XXXX	Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	40-50%
diiron trioxide	CAS-No.: 1309-37-1 EC No.: 215-168-2		5-10%
2-ethylhexanoic acid, zirconium salt	CAS-No.: 22464-99-9 EC No.: 245-018-1	Repr. 2 - H361d	0.1-0.9%
pentaerythritol	CAS-No.: 115-77-5 EC No.: 204-104-9		0.1-0.9%
Carbon black	CAS-No.: 1333-86-4 EC No.: 215-609-9		0.1-0.9%
Cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7 EC No.: 205-250-6 REACH Reg No.: 01-2119524678-29-XXXX	Eye Irrit.2A - H319, Skin. Sens 1 A- H317, Repr. 1B- H360, Aquatic Acute 1 - H400, Aquatic Chronic 3 - H412	0.1-0.9%
nonane	CAS-No.: 111-84-2 EC No.: 203-913-4	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 3- H226, STOT SE 3 - H336	<0.1%
propionic acid	CAS-No.: 79-09-4 EC No.: 201-176-3	Skin Corr. 1B - H314	<0.1%
octane	CAS-No.: 111-65-9 EC No.: 203-892-1	Aquatic Chronic 1 - H410, Skin Irrit.2 - H315, Asp. Tox - H304, Flam. Liq 2- H225, STOT SE 3 - H336	<0.1%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

Proprionic Acid: Specific Concentration Limits - Eye Irrit. 2; H319: 10 % <= C < 25 %, STOT SE 3; H335: C >= 10 %, Skin Corr. 1B; H314: C >= 25 %, Skin Irrit. 2; H315: 10 % <= C < 25 %.

Cobalt bis(2-ethylhexanoate): M (acute) = 1.

Section 4: First aid measures

Inhalation

4.1 Description of first aid measures

General information Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if

symptoms persist, always call a doctor. Seek medical attention for all eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue. If this product is inhaled and symptoms occur, move the exposed person to fresh air promptly. If breathing is difficult, give oxygen. If breathing has stopped or the exposed person experiences difficulty in breathing, administer artificial respiration and seek

immediate medical assistance.

IngestionRinse mouth thoroughly. Provide fresh air, warmth and rest. Do not induce vomiting. Never give anything by mouth if victim is unconscious, is rapidly losing consciousness or is

convulsing. Seek medical advice (show the label where possible). If vomiting occurs, the head should be kept low so that stomach content doesn't enter the lungs.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

the skin immediately with soap and water. Get medical attention if any discomfort continues

after rinsing.

Eye contact Do not rub eye. Avoid contaminating unaffected eye. Remove contact lenses if present and

easy to do so. Promptly wash eye(s) with plenty of water while lifting the eye lids. Rinse with

a gentle stream water for at least 15 minutes. Get prompt medical attention.

4.2 Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Exposure to product spray mists may be irritating to the respiratory system. Inhalation of

vapours may cause headache, fatigue, dizziness and central nervous system effects.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting.

Skin contact Prolonged contact may cause redness, irritation and dry skin. May cause an allergic skin

reaction.

Eye contact May cause temporary eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician Treat symptomatically.

Section 5: Firefighting measures

5.1 Extinguishing media

Extinguishing mediaUse extinguishing measures that are appropriate to local circumstances and the surrounding

environment. Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing media High volume water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Unusual fire & explosion hazards

Specific hazards

When heated, toxic and corrosive vapours/gases may be formed

No unusual fire or explosion hazards noted. If heated, harmful vapours may be formed.

5.3 Advice for firefighters

Special fire fighting procedures Avoid breathing fire vapours. Keep up-wind to avoid fumes. Fight advanced or massive fires

from safe distance or protected location. Do not scatter spilled material with more water

than needed to fight the fire Do not get water inside container

Protective equipment for firefighters Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard

EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Wear protective clothing as described in Section 8 of this safety data sheet. Do not smoke,

use open fire or other sources of ignition. Make safe all sources of ignition. Avoid contact with skin and eyes. Ensure adequate ventilation. Use non-sparking hand tools and explosion

proof electrical equipment. Avoid inhalation of dust and vapours

For emergency responders Follow safe handling advice and personal protective equipment recommendations for normal

 $use\ of\ product.$

6.2 Environmental precautions

Environmental precautions Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled

discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency

or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Spill clean up methods Stop leak if possible without risk. Wear necessary protective equipment. Absorb spillage with

non-combustible, absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled

container. Wash thoroughly after dealing with a spillage.

6.4 Reference to other sections

Reference to other sections See section 1 for emergency contact. For personal protection, see section 8 For waste

disposal, see section 13.

Section 7: Handling and storage

7.1 Precautions for safe handling

Handling

Read and follow manufacturer's recommendations. Do not handle broken packages without protective equipment. Avoid spilling, skin and eye contact. Do not use contact lenses. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Observe occupational exposure limits and minimise the risk of inhalation of vapours and mist. Ensure adequate ventilation. Vapours are heavier than air and may spread along floors. Do not eat, drink or smoke when using the product.

7.2 Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a dry, cool and well-ventilated place. Keep

upright. Keep locked up and out of reach of children. Avoid storing for very long periods.

Keep container tightly sealed when not in use.

 ${\bf Storage\ class} \qquad \qquad {\bf Flammable\ liquid\ storage}.$

7.3 Specific end use(s)

Specific end use(s)The identified uses for this product are detailed in Section 1.Usage descriptionUse only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection


8.1 Control parameters

Component	STD	TWA (8 Hrs)		STEL (15mins)		Notes
diiron trioxide	OEL		5 mg/m ³		10 mg/m ³	
diiron trioxide	OEL		10 mg/m ³			
diiron trioxide	OEL		4 mg/m ³			
pentaerythritol	OEL		10 mg/m ³		20 mg/m ³	
pentaerythritol	OEL		4 mg/m ³			
Carbon black	OEL		3 (I) mg/m ³			
nonane	OEL	200 ppm	1050 mg/m ³			
propionic acid	OEL	10 ppm	31 mg/m ³	20 ppm	62 mg/m ³	IOELV
octane	OEL	300 ppm	1450 mg/m ³	_		_

Ingredient comments

Ireland, Occupational Exposure Limits 2021.

8.2 Exposure Controls





Engineering measures Provide adequate ventilation, including appropriate local extraction, to ensure that the

defined occupational exposure limit is not exceeded.

Respiratory equipmentWhere risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN143 should be used, and suitable respirator cartridges as a backup to

conforming to EN143 should be used, and suitable respirator cartridges as a backup to engineering controls. Use type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. Use respirators and components tested and approved under

appropriate government standards such as CEN (EU).

Hand protectionUse suitable protective gloves if there is a risk of skin contact. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product.

Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Change gloves regularly. Suggested material: Nitrile rubber gloves.

Minimum breakthrough time / gloves: 480 min. Minimum layer thickness: 0.7mm.

Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as ${\tt EN}$

166(EU).

Other protection Protective clothing should be selected based on the task being performed and the risks

involved and should be approved by a specialist before handling this product. The selected

clothing must satisfy the European norm standard EN 943.

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before

eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or

smoke.

Process conditions Keep container tightly sealed when not in use. Ensure that eye flushing systems and safety

showers are located close by in the work place.

Section 9: Physical and chemical properties

Eye protection

9.1 Information on basic physical and chemical properties

Appearance Viscous liquid.

Colour Red

Odour Hydrocarbon, (slight).

Odour threshold - lower No information available as testing has not been completed.

Odour threshold - upperNo information available as testing has not been completed.

pH-Value, Conc. Solution Not applicable.

pH-Value, Diluted solution Not applicable.

Melting point May start to solidify at the following temperature: -15°C This is based on data for the

following ingredient: Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2%

aromatics. Weighted average: -58.56°C $\,$

Initial boiling point and boiling

range

>142°C

Flash point Closed cup 42°C

Evaporation rate Highest known value: 0.04 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2%

aromatics) Weighted average: 0.03 compared with butyl acetate

Flammability state Liquid

Flammability limit - lower(%) Greatest known range: Lower: 0.6% (Hydrocarbons, C10-C13, nalkanes, isoalkanes, cyclics, <

2% aromatics)

Flammability limit - upper(%) Greatest known range:Upper: 7% (Hydrocarbons, C10-C13, nalkanes, isoalkanes, cyclics, <

2% aromatics)

Vapour pressure Highest known value: 0.1 to 0.3 kPa (0.8 to 2.3 mm Hg) (at 20°C) (Naphtha(petroleum),

hydrotreated heavy). Weighted average: 0.16 kPa (1.2 mm Hg) (at 20 $^{\circ}\text{C})$

Vapour density (air=1) Highest known value: 4.5 (Air = 1) (Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <

2% aromatics).

Relative density 1.06

Bulk density No information available as testing has not been completed.

Solubility Insoluble in cold water

Decomposition temperature Stable under normal handling and storage conditions.

Partition coefficient; n-

Octanol/Water

No information available as testing has not been completed.

Auto ignition temperature (°C) Lowest known value: >230°C (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2%

aromatics).

Viscosity Kinematic (40°C): >0.22 cm²/s

Explosive properties Not classified as explosive.

Oxidising properties The product does not meet the criteria to be classified as oxidising.

9.2 Other information

Molecular weight No information available as testing has not been completed.

Volatile organic compound 432.00 g/litre

Other information Weight Solids: 52.0% +/- 1.0%

Volume solids: 42.0% +/- 1.0%.

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity Reactions may occur with strong oxidising agents.

10.2 Chemical stability

Stability Stable under normal temperature conditions and recommended use.

10.3 Possibility of hazardous reactions

Hazardous reactions For information on hazardous reaction see section 10.1.

Hazardous polymerisationUnknown.Polymerisation descriptionUnknown.

10.4 Conditions to Avoid

Conditions to avoid Avoid exposure to high temperatures or direct sunlight. Avoid heat, flames and other sources

of ignition.

10.5 Incompatible materials

Materials to avoid Do not mix with other chemicals unless listed on directions. Strong oxidising substances.

10.6 Hazardous decomposition products

Hazardous decomposition products When heated, vapours/gases hazardous to health may be formed

Section 11: Toxicological information

11.1 Information on hazard classses as defined in Regulation (EC) No. 1272/2008

Toxicological information No toxicological information for the overall finished product.

Acute toxicity (Oral LD50)No information available as testing has not been completed.Acute toxicity (Dermal LD50)No information available as testing has not been completed.Acute toxicity (Inhalation LD50)No information available as testing has not been completed.

Serious eye damage/irritation Product is not classified as an eye irritant.

Skin corrosion/irritation The product is not classified as a skin corrosion/irritation hazard.

Respiratory sensitisationThe product is not classified as a respiratory hazard. **Skin sensitisation**The product is classified as a skin sensitisation hazard.

Germ cell mutagenicity The product is not classified as a mutagen.

Carcinogenicity The product is not classified as a carcinogen hazard.

Specific target organ toxicity - Single exposure:

STOT - Single exposure The product is classified as a single exposure specific target organ toxin.

Specific target organ toxicity - Repeated exposure:

STOT - Repeated exposureThe product is not classified as a repeat exposure specific target organ toxin.

Inhalation Exposure to product spray mists may be irritating to the respiratory system. Inhalation of

vapours may cause headache, fatigue, dizziness and central nervous system effects.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting.

Skin contact Prolonged contact may cause redness, irritation and dry skin. May cause an allergic skin

reaction.

Eye contact May cause temporary eye irritation.

Waste management When handling waste, consideration should be made to the safety precautions applying to

handling of the product.

Routes of entry Eyes, skin, ingestion or inhalation.

Target organs Eyes, skin, digestive system, respiratory system.

Aspiration hazards: The product is not classified as an aspiration hazard. **Reproductive toxicity:** The product is not classified as a reproductive hazard.

Name	LD50 oral	LD50 dermal	LD50 inhalation
nonane			3200.00ppmV Rat 4 Hours17000.00mg/m-3 Rat 4 Hours
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>5000.00mg/kg Rat	>5000.00mg/kg Rabbit	>6.10mg/l (vapours) Rat 4 Hours
2-ethylhexanoic acid, zirconium salt	>5.00g/kg Rat	>5.00g/kg Rabbit	
propionic acid	2600.00mg/kg Rat	525.00mg/kg Rabbit	
octane			25260.00ppmV Rat 4 Hours118.00g/m3 Rat 4 Hours

11.2 Information on other hazards

Information on other hazards None known.

Section 12: Ecological information

12.1 Toxicity

Acute toxicity - FishNo information available as testing has not been completed.Acute toxicity - Aquatic invertebratesNo information available as testing has not been completed.Acute toxicity - Aquatic plantsNo information available as testing has not been completed.Acute toxicity - MicroorganismsNo information available as testing has not been completed.Chronic toxicity - FishNo information available as testing has not been completed.Chronic toxicity - AquaticNo information available as testing has not been completed.

inverteb rates

Chronic toxicity - Aquatic plants

No information available as testing has not been completed.

No information available as testing has not been completed.

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude

the possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

Eco toxilogical information Not classified as dangerous for the environment according to the criteria of Regulation (EC)

No 1272/2008.

12.2 Persistence and degradability

DegradabilityThe degradability of the product has not been stated.Biological oxygen demandNo information available as testing has not been completed.Chemical oxygen demandNo information available as testing has not been completed.

12.3 Bioaccumulative potential

Bioaccumulative potentialNo data available on bioaccumulation.Bioaccumulation factorNo information available as testing has not been completed.Partition coefficient; n-No information available as testing has not been completed.Octanol/Water

12.4 Mobility in soil

Mobility Insoluble in cold water.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB Substances.

12.6 Endocrine disrupting properties

Endocrine disrupting propertiesThe product does not contain any substances with endocrine disrupting properties at a

concentration above or equal to 0.1%.

12.7 Other adverse effects

Other adverse effects None known.

Name	IACIITA TOVICITY (FIGN)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
lalkande legalkande cvclice <	- 1 1	LC50 48 Hours >100.00ppm Daphnia magna	
propionic acid	iOnchornvnchus mykiss (Raindow	EC50 48 Hours 22.70ppm Daphnia magna	EC50 96 Hours 43.00mg/l
diiron trioxide	ILCO 96 Hours >10000.00mg/l	EC50 48 Hours >100.00mg/l Daphnia magna	EC0 96 Hours >5000.00mg/l

Section 13: Disposal considerations

Waste management When handling waste, consideration should be made to the safety precautions applying to

handling of the product.

13.1 Waste treatment methods

Disposal methods Dispose of waste and residues in accordance with local authority requirements, and in

accordance with all local, national and international regulations.

Section 14: Transport information

14.1 UN number or ID number

 UN no. (ADR)
 UN1263

 UN no. (IMDG)
 UN1263

 UN no. (IATA)
 UN1263

14.2 UN proper shipping name

ADR proper shipping name PAINT OF PAINT RELATED MATERIAL IMDG proper shipping name PAINT OF PAINT RELATED MATERIAL IATA proper shipping name PAINT

14.3 Transport hazard class(es)

ADR class 3
IMDG class 3
IATA class 3

Transport labels



14.4 Packing group

ADR/RID/ADN packing group III
IMDG packing group III
IATA packing group III

14.5 Environmental hazards

ADR No IMDG No IATA No

14.6 Special precautions for user

EMS F-E, S-E
Emergency action code A3 A72 A192
Hazard no. (ADR) 30
Tunnel restriction code (D/E)

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture

EU legislation Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Reach Regulation (EC) No 453/2010. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and

Restriction of Chemicals (REACH).

Approved code of practice 2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents)

Regulations (2001-2021) and the Safety, Health and Welfare at Work (Carcinogens)

Regulations (2001-2019)

15.2 Chemical safety assessment

Chemical safety assessment No chemical safety assessment has been carried out.

Section 16: Other information

General information This Safety Data Sheet is in accordance with REACH Annex II, (EC) No 2020/878.

Revision comments [1]Information updated. [2]Information updated. [3]Information updated. [8]Information

updated. [9]Information updated. [10]Information updated. [11]Information updated.

[12]Information updated. [15]Information updated. This is a third issue.

Revision date 15 January 2021

Revision

Safety data sheet status Approved.

Hazard statements in full

EUH066 Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H302 Harmful if swallowed.H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

H361 Suspected of damaging fertility or the unborn child.

H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child .
H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H315 Causes skin irritation.

H410 Very toxic to aquatic life with long lasting effects.

H314 H225 Causes severe skin burns and eye damage. Highly flammable liquid and vapour.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.